



Grab bar:

- Model SA70-001180 (18" long) **Bradex**[®]
- Model SA70-001240 (24" long) **Bradex**[®]
- Model SA70-001360 (36" long) **Bradex**[®]
- Model SA70-001420 (42" long) **Bradex**[®]
- Model SA70-002600 (60" long)

Product Materials

FLANGES: 3/8" dia. 11 gauge stainless steel, with exposed surfaces in architectural satin finish.

TUBING: 1 1/2" O.D. 18 gauge stainless steel, seamless construction with exposed surfaces in architectural satin finish. Bent ends of tubing pass through the flanges and are welded into a single structural unit for maximum strength. Intermediate supports are contour cut and joined by welding to form an integral part of the grab bar. All welds ground and polished to blend. Mandrel bending process maintains uniform bar diameter. Return provides 1 1/2" standard safety clearance between wall and bar.

CLOSURE PLATE: 11 gauge stainless steel.

Strength

When properly mounted, all Bradley heavy duty grab bar systems meet or exceed the requirements of ANSI Standard A117.1, the ADA and ABA Accessibility Guidelines for Buildings and Facilities (ADAAG) and the Uniform Federal Accessibility Standard (UFAS). Select dimensions of configurations (-001, -058 and -059) are IAPMO certified to support up to 1000 pounds. See configurations on table below. All other SA70 grab bars outside of these parameters are rated to support up to 250 pounds. Wall must be reinforced in the area of the grab bar in order to support the load it is intended to support.

Guide Specification

Security grab bar shall be fabricated of 1 1/2" O.D. satin finish stainless steel with exposed mounting flanges and 11 gauge stainless steel closure plate in sizes and configurations as indicated. Furnished with torx-head mounting screws.

Installation

For instructions on installation, warnings and maintenance, please visit www.bradleycorp.com.


ADA Compliant

- Consult local and national accessibility codes for proper installation guidelines.
- Conformity and compliance to local and national codes is the responsibility of the installer.

Optional Features

Feature	Suffix
<input type="checkbox"/> Safety-grip finish	-2

Orders composed of products indicated as **Bradex**[®] will be available to ship in three days after receipt of order at the factory. There is no pricing penalty for this service from Bradley.



Configuration Information - Bariatric Models

⚠ WARNING Only models/configurations listed in the configurations information table have been rated for use up to 1000 pounds.

		OD	1-1/2"
		Rating (LBS)	1000
Configuration Number	Grab Bar Length	SA70	
001-12	12"	X	
001-18	18"	X	
001-24	24"	X	
001-36	36"	X	
001-42	42"	X	
001-54	54"	X	
059/058	up to 42" x 54"	X	

Bradex[®] Item - Standard Finish