



- Standard Series — Satin Finish
- Recessed
- ADA Compliant

### Product Materials

**FRONT PANEL/ FLANGE:** 22 gauge stainless steel with exposed surfaces in architectural satin finish. One-piece seamless construction, 5/8" wide with 1/4" return.

**CABINET:** 22 gauge stainless steel.

**SOAP VESSEL:** 22 gauge stainless steel with exposed surfaces in architectural satin finish. Tumbler lock keyed like other Bradley units.

**SOAP VESSEL LINER:** low density polyethylene.

**SOAP VALVE:** chrome-plated brass with ABS mechanism. Requires less than 5 lbs. of force to dispense soap.

### Capacity

40-oz. liquid soap.

### Operation

Soap dispenser swings open for filling and cleaning. Sight gauge indicates refill time. Valve dispenses measured amount of liquid soap. Requires less than 5 lbs. of force to dispense soap.

- Bradley liquid soap valves operate best with any vegetable oil or coconut oil hand soap having a 10–15% soap concentration.

### Installation

Verify all rough-in dimensions prior to installation. Requires rough wall opening 67/8"W x 113/4"H x 4"D. Secure to framing with mounting screws (included) at holes provided. Shim at screw points as required.

### Guide Specification

Recessed liquid soap dispenser shall be fabricated of 22 gauge stainless steel with exposed surfaces in satin finish. Requires less than 5 lbs. force to dispense soap. Capacity: 40-oz. liquid soap.

**Overall dimensions: 73/4"W x 125/8"H x 41/16"D.**

### ADA Compliant

- Consult local and national accessibility codes for proper installation guidelines.
- Conformity and compliance to local and national codes is the responsibility of the installer.

