



Rough Wall Opening
6" (152mm) Wide
12" (3051mm) High
4" (102mm) minimum
recessed depth

CONSTRUCTION:

Fabricated of Type 304 stainless steel with exposed surfaces having #4 satin-finish. One piece seamless door construction, 20-gauge (0.81mm) with 3/4" (19mm) return for rigidity. Door is mounted to cabinet with 2 rivets and is provided with stainless steel handle and stainless steel cable door swing limiter. Stainless steel inner container mounts on front door and lifts out for servicing. All welded construction.

CAPACITY:

0.6-gallon (2.3-L) removable stainless steel receptacle.

INSTALLATION:

Provide framed wall opening. Recessed depth required from finish face of wall is 4" (102mm). Check plans and coordinate with mechanical engineer to avoid protrusion from opposite wall, pipes, conduits, electrical wiring etc. If installing in plaster wall, recommend grounding. If installing where unit projects above top of wainscot, provide filler to prevent gap from finished wall and flange of unit. If installing in block walls, use metal expansion shields. 1/8" (3mm) gap recommended between units for door clearance.

OVERALL DIMENSIONS:

8-1/32" W x 14-1/32" H x 4-7/16" D (204 x 356 x 113mm)

Recessed Coverall Sanitary Napkin Disposal shall be Model ND-3 of Gamco Commercial Restroom Accessories, One Gamco Place, Durant, OK, 74701-1910