



## **STAINLESS STEEL & EMBOSSED STAINLESS STEEL Metal Toilet Partitions**

### **M a i n t e n a n c e   P r o c e d u r e**

#### **1 . 0 1      S t a i n l e s s   S t e e l   &   E m b o s s e d   S t a i n l e s s   S t e e l**

---

- 1** The best method of maintaining your high quality Hadrian Stainless Steel and Embossed Stainless Steel toilet partitions is frequent regular cleaning. Surfaces should be cleaned with a mild detergent or ammonia solution, rinsed with clear water (preferably warm/hot) and wiped dry. Never attempt to clean stainless steel with a steelwool cleaning pad, wire brush, or cleaning agents containing harsh abrasives.
  
- 2** If dirt build-up must be removed, use a metal cleaner specifically recommended for stainless steel. Deposits which require scouring may be removed with a mild abrasive powder such as the household cleaner, Ajax. Grease, oil and/or fingerprints may be removed with detergent and water, plus a solvent (i.e. acetone, kerosene, mineral spirits, etc.). Be sure to rub in the direction of the grain of the metal.
  
- 3** It is important to rinse stainless steel with clear water and wipe the surfaces with a soft cloth after cleaning to remove all traces of the cleaning agent. Again, rubbing and wiping should be done in the direction of the polished lines, not against them.
  
- 4** For any other assistance in maintaining the “bright look” of Stainless Steel and Embossed Stainless Steel toilet partitions, please call your local Hadrian representative.
  
- 5** If your partitions have a continuous hinge, regular application of an LPS II or an industrial type, non-drying lubricant is recommended.